



UNITED KINGDOM

Basic Specification

60	1 x Pre-Owned ESE 6 RD 8000 Suction Excavator Mounted on a DAF CFM350 MX-13 Chassis Cab RHD	1 pc
----	--	------

Technical Details – Mileage and Fan/Compressor Hours correct as at 14.11.2025

Year of Manufacture	2024
Fuel Tank Capacity	1 x 300 litre / 1 x 250 litre
Present Mileage	12,710.14 miles
Fan Hours	396:15 hours
Compressor Hours	249:01 hours

A Suction Capacities		
A210	High Performance (DV2) Twin Fan Qmax = 42,000 m³/hr, Pmax = 40,000 Pa, optimized version	1 pc
B Separation System		
B006	RSP Separation System	Included
B016	Fine Filter Unit with automated compressed air cleaning system	Included
B086	8m³ Container including abrasion protection inside and stainless steel drip edge. Tipping to the right side when viewed from the rear.	Included
C Hose Carrier		
C406	Articulated Suction Hose Carrier 6000, swivel motor Range 6,000 mm - Slewing range 180 degrees Fitted to the left side when viewed from the rear Including 2 LED work lights mounted on the hose carrier	1 pc
C416	Lift and slew control system for suction hose carrier	1 pc
C426	Sensors with visual and audible warning system in the cab to indicate the transport position of the suction hose carrier	1 pc
D Working Area		
D020	PE suction nozzle, RSP - clamp system L = 1,230 mm, D = 250 mm, incl. holder and 2 RSP-clamps	1pc
D320	PE Reducing Suction Nozzle (non-conductive) L = 1,360 mm, D = 250/130 mm (RSP Clamping System)	1 pc
D410	PU Suction Hose Extension with steel coupling L = 2,200 mm, D = 250 mm	1 pc
E Hydraulic System		
E000	Hydraulic system for energy-efficient use	Included
E100	Ultra fine bypass filter in the return line	1 pc
E410	External hydraulic outlet Pmax = 160 bar, with inlet and return flow	1 pc
E420	Installation of external hydraulic outlet Pmax = 160 bar, with inlet and return flow on the articulated hose carrier for hydraulically driven equipment	1 pc
F Pneumatic System		
F000	Air connections on the back for oiled and non-oiled pressurised air	Included
F200	Air Compressor Qmax = 4,5 m³/min Pmax = 7 bar radio remote controlled	1 pc
F400	Stainless steel hose reel with spring return including an 8m hose, 19mm diameter	2 pc
H Control System		
H000	Entire superstructure is controlled by PLC Display including constant monitoring system showing machine data	Included



UNITED KINGDOM

H Control System (Continued)		
H020	Remote control unit that operates superstructure functions including spare transmitter, battery and battery charger	Included
H031	RSP Connect system for monitoring of superstructure data including 24-month contract	Included
H040	Programme adjustment to move the articulated suction hose carrier in two stages (slow/fast), switchable at the rear of the vehicle	Included
I Additional Equipment		
I000	Exhaust air silencer frequency optimised for RSP Suction Excavators to reduce noise levels	Included
I016	Two lockable storage compartments made from stainless-steel and mounted on the offside of the vehicle	Included
I020	Safety equipment (PPE)	Included
I030	Electrical Spare Parts Kit	Included
I100	Hose rack between cab and superstructure (Space for 1 x 2,200 mm & 1 x 1,500 mm PU suction hose)	1 pc
K Safety Equipment / Industrial Equipment		
K000	Emergency stop button with large mushroom head	Included
K010	Stabiliser leg support sensor system including visual and audible warning system in the driver's cab	Included
K020	Airflow gate for DV2 Twin Fan	Included
K030	Central lubrication system for the DV2 Twin Fan	Included
K630	6kg dry powder hand operated fire extinguisher with protective cabinet	1 pc
RSP02	Rear ladder and grab handles to be supplied as a spare part for chassis supplier to fit at customer's request	1 pc
L Illuminating Equipment / Warning Devices		
L000	LED flashing beacon mounted at the rear of the vehicle	Included
L010	LED Work lamp mounted at the rear of the vehicle	Included
L020	LED Marker lights positioned on the lid	Included
M Design		
M000	Paintwork of Suction Superstructure in high gloss colour and Hose Carrier in textured paint	Included
COLOUR	DAF White H3279WHITE	Included
M226	Side cladding on the container in 4mm aluminium plate for advertising purposes, tilting side same angle as the tilting shaft	1 pc
N Equipment for loosening the ground		
N200	Pneumatic Venturi Air Knife (non-conductive)	1 pc
N310	Pneumatic 1" Air Lance L = 2,000 mm (non-conductive)	1 pc
N801	Additional Hand Tools:- 2m Spade for cleaning container 2 Scrapers Pinch Bar Grease Gun Rubber Hammer Oil Discharge Hose	1 pc
O Handing over / Instruction		
O010	Documentation and operator's manual	Included
O020	Access authorisation to the RSP online spare parts catalogue	Included
O130	Starting-up / Registration including superstructure approval by Dekra	1 pc



UNITED KINGDOM

P100 Vehicle Chassis		
P100	DAF CF530 FAW RHD Chassis Cab including:- Audible Left Turn warning with side scanners Reverse & Side Camera System 1.2 Metre LED roof mounted Blaze Bar Blind Spot Information System (DVS2024) Moving Off Information System (DVS2024)	1 pc
Q Chassis Options		
Q100	Installation of the side under-run guards	1 pc
Q110	Installation of the rear under-run guards	1 pc
Q411	Installation of one aluminium checker-plate mudguard (one axle)	3 pc
Q510	Additional aluminium fuel tank (maximum 300 litres subject to confirmation)	1 pc
Q700	Repositioning of the four-circuit protection valve & air tanks	1 pc
Q910	Preparations of the DAF vehicle chassis by DAF Germany	1 pc

PRICING SUMMARY	
1 x Pre-Owned ESE 6 RD 8000 Suction Excavator Mounted on a DAF CFM350 MX-13 Chassis Cab RHD	£409,500.00 + VAT