

Basic Specification

60 1 x Pre-Owned ESE 6 RD 8000 Suction Excavator

1 pc

Mounted on a Mercedes-Benz Arocs 5 3251 8x4x4 Chassis Cab LHD

Technical Details - Mileage and Fan/Compressor Hours correct as at 14.11.2025

Year of Manufacture2023Fuel Tank Capacity1 x 300 litre / 1 x 250 litrePresent Mileage12,104 milesFan Hours284:03hoursCompressor Hours152:26 hours

^	Suction Conscition	
Α	Suction Capacities	
A210	High Performance (DV2) Twin Fan Qmax = 42,000 m³/hr, Pmax = 40,000 Pa, optimized version	1 pc
A220	Increased Performance of A210 (DV2) Twin Fan	
A230	Variable adjustment of suction power below the 1st working speed of the fan	1 pc
В	Separation System	
B006	RSP Separation System	Included
B016	Fine Filter Unit with automated compressed air cleaning system Include	
B086	Tilting container volume 8 m³, abrasion protection, 1 pcs for one-side tipping, tilting axis height 2.000 mm Tipping to the LEFT side when viewed from the rear.	Included
B506	Heavy duty version of the lid Baffle plate and entry of the lid lined with highly wear resistant material	1 pc
С	Hose Carrier	
C406	Articulated Suction Hose Carrier 6000, swivel motor Range 6,000 mm - Slewing range 180 degrees	1 pc
	Fitted to the RIGHT side when viewed from the rear	
C416	Lift and slew control system for suction hose carrier	1 pc
C416		1 pc
	Lift and slew control system for suction hose carrier	1 pc
D	Lift and slew control system for suction hose carrier Working Area Suction nozzle galvanized, RSP - clamp system	
D D010	Lift and slew control system for suction hose carrier Working Area Suction nozzle galvanized, RSP - clamp system L = 1,230 mm, D = 250 mm, incl. holder and 2 RSP-clamps Transport holder for Extensions (Galvanized)	1 pc
D D010 D700	Lift and slew control system for suction hose carrier Working Area Suction nozzle galvanized, RSP - clamp system L = 1,230 mm, D = 250 mm, incl. holder and 2 RSP-clamps Transport holder for Extensions (Galvanized) Length up to 1,500 mm	1 pc
D D010 D700	Lift and slew control system for suction hose carrier Working Area Suction nozzle galvanized, RSP - clamp system L = 1,230 mm, D = 250 mm, incl. holder and 2 RSP-clamps Transport holder for Extensions (Galvanized) Length up to 1,500 mm Hydraulic System	1 pc
D D010 D700 E E000	Lift and slew control system for suction hose carrier Working Area Suction nozzle galvanized, RSP - clamp system L = 1,230 mm, D = 250 mm, incl. holder and 2 RSP-clamps Transport holder for Extensions (Galvanized) Length up to 1,500 mm Hydraulic System Hydraulic system for energy-efficient use	1 pc 1 pc Included



UNITED KINGDOM

CHILD	KINGDOM
Pneumatic System	
Air connections on the back for oiled and non-oiled pressurised air	
Air Compressor Qmax = 4,5 m³/min Pmax = 7 bar radio remote controlled	1 pc
Stainless steel hose reel with spring return including an 8m hose, 19mm diameter	1 pc
Water System	
High pressure water system including a stainless steel hose reel, radio remote controlled - Pmax = 200 bar Qmax = 21 l/min	1 pc
400 litre unpressurised plastic water tank including overflow	1 pc
Control System	
Entire superstructure is controlled by PLC Display including constant monitoring system showing machine data	Included
Remote control unit that operates superstructure functions including spare transmitter, battery and battery charger	Included
RSP Connect system for monitoring of superstructure data including 24-month contract	Included
Programme adjustment to move the articulated suction hose carrier in two stages (slow/fast), switchable at the rear of the vehicle	Included
Additional Equipment	
Exhaust air silencer frequency optimised for RSP Suction Excavators to reduce noise levels	Included
Storage compartment made of stainless steel for tools and accessories below the tilting axis of the container, two-door and lockable	Included
Safety equipment (PPE)	Included
Electrical Spare Parts Kit	Included
Hose rack between cab and superstructure (Space for 1 x 2,200 mm PU suction hose)	1 pc
Additional equipment hose rack: left side - holder for 16 traffic side cones right side - storage box	1 pc
Hydraulic Drives/Intermediate Gearboxes	
RSP Drive No.1 including safety system System designed for low speeds and short travel distances	1 pc
Electrical RSP Steering system	1 pc
Safety Equipment / Industrial Equipment	
Emergency stop button with large mushroom head	Included
Stabiliser leg support sensor system including visual and audible warning system in the driver's cab	Included
Airflow gate for DV2 Twin Fan	Included
Central lubrication system for the DV2 Twin Fan	Included
	Air connections on the back for oiled and non-oiled pressurised air Air Compressor Qmax = 4,5 m³/min Pmax = 7 bar radio remote controlled Stainless steel hose reel with spring return including an 8m hose, 19mm diameter Water System High pressure water system including a stainless steel hose reel, radio remote controlled - Pmax = 200 bar Qmax = 21 l/min 400 litre unpressurised plastic water tank including overflow Control System Entire superstructure is controlled by PLC Display including constant monitoring system showing machine data Remote control unit that operates superstructure functions including spare transmitter, battery and battery charger RSP Connect system for monitoring of superstructure data including 24-month contract Programme adjustment to move the articulated suction hose carrier in two stages (slow/fast), switchable at the rear of the vehicle Additional Equipment Exhaust air silencer frequency optimised for RSP Suction Excavators to reduce noise levels Storage compartment made of stainless steel for tools and accessories below the tilting axis of the container, two-door and lockable Safety equipment (PPE) Electrical Spare Parts Kit Hose rack between cab and superstructure (Space for 1 x 2,200 mm PU suction hose) Additional equipment hose rack: left side - holder for 16 traffic side cones right side - storage box Hydraulic Drives/Intermediate Gearboxes RSP Drive No.1 including safety system System designed for low speeds and short travel distances Electrical RSP Steering system Safety Equipment / Industrial Equipment Emergency stop button with large mushroom head Stabiliser leg support sensor system including visual and audible warning system in the driver's cab Airflow gate for DV2 Twin Fan



UNITED KINGDOM

	ONTER	KINGDOW
K	Safety Equipment / Industrial Equipment (Continued)	
K100	K100 – RSP Rear view camera - Use of the original Chassis Navigation-System - Mounting of Original rearview-camera	1 pc
K200	Earthing system including control unit, ground stake and cable reel	
K330	Additional emergency stop button mushroom head	1 pc
K510	O Optical signal in cab display for axle load measuring device	
K630	0 6kg dry powder hand operated fire extinguisher protective cabinet	
K800	Support with large pressure plates	1 pc
L	Illuminating Equipment / Warning Devices	
L000	LED flashing beacon mounted at the rear of the vehicle	Included
L010	LED Work lamp mounted at the rear of the vehicle 1x in the rear mid position 2x onto boom	Included
L020	LED Marker lights positioned on the lid	Included
L100	Two additional LED work lamps 2x LED spot below fan-house, right + left Switch in cabin + rear 2x LED spot in the rear, next to rear lights, right + left Switch in cabin + rear 2x LED spot in the rear, on lid, left and right	1 pc
L110	LED Work lamp with magnetic base including a cable reel mounted at the rear of the vehicle	1 pc
L200	Two LED Strobe lights mounted at the front of the vehicle	1 pc
L200	Two LED Strobe lights mounted at the rear of the vehicle	1 pc
L226	LED Periphery lighting (Four LED Spotlights, to be mounted both sides of the lid)	1 pc
L236	LED Lighting inside the storage compartment	1 pc
M	Design	
M000	Paintwork of Suction Superstructure in high gloss colour and Hose Carrier in textured paint - MB7194 Mouse Grey	Included
M226	Side cladding on the container in 4mm aluminium plate for advertising purposes, tilting side same angle as the tilting shaft	1 pc
SON2	Additional Equipment: - 2nd storage compartment on passengers side - LED lighting in 2nd storage compartment - Side cladding of rear supports	1 pc
N	Equipment for loosening the ground	
N801	Additional Hand Tools:- 2m Spade for cleaning container 2 Scrapers Pinch Bar Grease Gun Rubber Hammer Oil Discharge Hose	1 pc



	5111122	
P100	Vehicle Chassis	
P100	Mercedes Benz Arocs 5 3251 8x4x4 RHD Chassis Cab LHD including:- Blind Spot Information System (DVS2024) Moving Off Information System (DVS2024) Light Fix Top Bar and Beacon Brigade Electronics Rigid 4 camera system standard 1 with 4G Live View Brigade Electronics BBS white noise reverse alarm Right turn warning with speed switch wired through the indicator and night time cut out	1 pc
Q	Chassis Options	
Q100	Installation of the side under-run guards	1 pc
Q300	Reconstruction diesel tank	1 pc
Q510	Additional aluminium fuel tank	1 pc
Q700	Repositioning of the four-circuit protection valve & air tanks	1 pc
Z	Special Equipment	
Z250	RM VARIO, Rotating module for rotating all kinds of suction nozzle extension, to be coupled onto the hose carrier, incl. RSP-clamp and oscillation function	1 pc

PRICING SUMMARY		
1 x Pre-Owned ESE 6 RD 8000 Suction Excavator	£499,500.00 + VAT	
Mounted on a Mercedes-Benz Arocs 5 3251 8x4x4 Chassis Cab RHD		